### **SCHUKO CLASSIC**

### **BOWAmaxi SOCKET OUTLETS**





#### **COVER**

with hinged lid stainless steel, matt drip-proof IP41

| ITEM NO. | WEIGHT<br>g/EACH | PU |
|----------|------------------|----|
| 1632ESM  | 498              | 1  |



#### **COVER**

with hinged lid platinum, matt drip-proof IP41

| ITEM NO. | WEIGHT<br>g/EACH | PU |
|----------|------------------|----|
| 1632PLM  | 498              | 1  |



#### **COVER**

with hinged lid brass, matt drip-proof IP41

| ITEM NO. | WEIGHT<br>g/EACH | PU |
|----------|------------------|----|
| 1632MSM  | 498              | 1  |



# THERMOPLASTIC DOUBLE SOCKET OUTLET

with double SCHUKO outlet

| ITEM NO. | WEIGHT<br>g/EACH | PU |
|----------|------------------|----|
| 1632602  | 281              | 1  |



## THERMOPLASTIC HOUSING BASE

| ITEM NO. | WEIGHT<br>g/EACH | PU |
|----------|------------------|----|
| 1632500  | 187              | 1  |

All standard socket outlets with an 80 mm cover and support ring fastening available for installation engineering, communication and telecommunications can be mounted into the 1632500 enclosure

Simple and safe connection with coupling brackets.

