

# SCHUKO PROFESSIONAL

## THREE-WAY CONNECTORS

2-pole +  $\oplus$ , 16 A 250 V, DIN/VDE 0620 and IEC 60884 compliant · for wires up to bis 3 x 2,5 mm<sup>2</sup> splash-proof IP54 ·  $\diamond$



### THREE-WAY SOLID RUBBER CONNECTOR

with voltage indicator  $\otimes$  and self-closing lid

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
black	1173503	426	5



### THREE-WAY SOLID RUBBER CONNECTOR

with voltage indicator  $\otimes$  and self-closing lid

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
red/black	1173543	426	5



### THREE-WAY SOLID RUBBER CONNECTOR

with voltage indicator  $\otimes$  and self-closing lid

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
grey/black	1173563	426	5

# SCHUKO PROFESSIONAL

## PRESSURISED WATER-IMPERMEABLE

2-pole +  $\oplus$ , 16 A 250 V, DIN/VDE 0620 and IEC 60884 · for wires up to bis 3 x 2,5 mm<sup>2</sup> pressurised water-impermeable IP68 ·  $\diamond$



### THERMOPLASTIC PLUG

with protective cap

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
blue	1979850	150	5



### THERMOPLASTIC CONNECTOR

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
blue	1976850	150	5



### THERMOPLASTIC PLUG

with protective cap

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
blue	1989850	130	5