

# LOW-VOLTAGE PLUGS AND SOCKET OUTLETS

according to IEC 60309, EN 60309, VDE 0623


**turn2fix**



## PLUG

splash-proof IP44

- screw terminals
- quick release locking system (turn2fix)
- nickel-plated contacts



POLES	2	3	2	3
AMPERE	16		32	

a	135	135	135	135
b	51	51	51	51
c	48	48	48	48
K	9,5-24	9,5-24	9,5-24	9,5-24
Weight [g/each]	142	160	142	160

VOLTAGE	24 V~	42 V~	24/42 V~
FREQUENCY	50/60 HZ	50/60 HZ	100-200 HZ
DESIGNATION	WITHOUT AUXILIARY NOTCH	12H	4H

AMPERE	POLES	ITEM NO.	ITEM NO.	ITEM NO.	PACKING UNIT
16	2	S01S20	S01S60	S01S10	10
16	3	S11S20	S11S60	S11S10	10
32	2	S02S20	S02S60	S02S10	10
32	3	S12S20	S12S60	S12S10	10


**turn2fix**



## PLUG

watertight IP67

- screw terminals
- quick release locking system (turn2fix)
- nickel-plated contacts



POLES	2	3	2	3
AMPERE	16		32	

a	124	131	146	152
b	79	87	93	100
c	48	48	48	48
K	9,5-24	9,5-24	9,5-24	9,5-24
Weight [g/each]	164	182	164	182

VOLTAGE	24 V~	42 V~	24/42 V~
FREQUENCY	50/60 HZ	50/60 HZ	100-200 HZ
DESIGNATION	WITHOUT AUXILIARY NOTCH	12H	4H

AMPERE	POLES	ITEM NO.	ITEM NO.	ITEM NO.	PACKING UNIT
16	2	S01S25	S01S65	S01S15	10
16	3	S11S25	S11S65	S11S15	10
32	2	S02S25	S02S65	S02S15	10
32	3	S12S25	S12S65	S12S15	10